



Dehumidifier

Performance Curve Chart



LG 195 Exterior Dimensions



Schematic Diagram of the Structure



LG 195



FEATURES:

- Compact yet powerful, the LEIZIG dehumidifier offers a versatile dehumidification range from 70-880pints/day.
- Boasting a high-efficiency filtration system, it ensures your plants are safeguarded from detrimental microbes.
- Experience industry-leading minimal noise operation.
- This dehumidifier is equipped with a remote dry contact input and an RS485, communication interface supporting the standard MODBUS protocol. It can seamlessly integrate with various humidity controllers and control systems.
- Choose from a variety of installation options including hoisting, ceiling, wall, and floor cabinets – there's a fit for every preference.

Model No.	LG 195
Factory ID No.	31000020
Dimensions(W*H*D)	32.9" * 24.4" * 23.8"
Package Dimensions(W*H*D)	36.3" * 29.6" * 27.5"
Technical Parameters	LG 195
Capacity	195 Pints/Day
Efficiency	7.0Pints/kWh
Refrigerant	R32
Operating Temp	41-100°F
Drain Connection	3/4 Threaded NPT
Air Filter	MERV-8/13;21.8"* 21.8"* 2"
Blower (Tested with duct collars on)	600 CFM @ 0.0" WG
Heat Load (BTU/H)	5150
Energy Factor	3.31 L/kwh
Electrical Parameters	LG 195
Supply Voltage	110-240VAC/1PH/50&60HZ
Power	1160W
Current Draw	10.2 @120V / 5.3 @230V
Attachment Parameters	LG 195
Weight	176lb
Weight (w/ Packaging)	260 lb
Maximum Noise	68dB(A)
Installation Method	Ceiling-suspended or Bottom fixed
Component Material	Galvanized Steel/Powder Electroplated Paint (stainless steel housing optional)
Safety Parameters	In Accordance with DIN 31001
Protection Level	IP23
Surface Color	RAL7035 (light grey) +RAL 1033 (Orange), other colors on request
Certification	CE/ETL

Accessories

Type	ID NO.	Description
IDK3	31800018	Intake Duct kit
EDK3	31800019	Exhaust Duct kit
FT308	31800031	Standard Filtration(MERV8)
FT313	31800034	Superior Filtration(MERV13)